

Tripod DB-A3 short

according to EN 795:2012 Typ B und CEN/TS 16415:2017



Product information:

Order No.:	Mounting diameter (B)	Height (H)	Transport length	Weight
41-49k	Ø 507 mm bis Ø 1606 mm	1132 mm bis 1909 mm	1225 mm	19 kg
40-58	OPTIONAL: Tripod Carrying and Protection Bag			
41 - xx	OPTIONAL: HRA retractable type fall arrester with rescue hoisting facility up to 40 m			

Features:

- Lightweight aluminum tripod
- Legs are adjustable in 3 different angles
- 3 deflection pulleys, inside, for cables from Ø 4.8 - 6 mm
- 3 separate anchorage points
- Corrosion resistant by coating
- Anchorage system for max. 3 persons
- equipped with foldable rubber feet
- Applicable with IKAR-Retractable Type Fall Arrester with rescue hoisting facility (Type HRA) up to 40m
- **optional** : HRA retractable type fall arrester with rescue hoisting facility up to 40 m
- **optional** : Tripod Carrying and Protection Bag

The assembly instructions for the tripods must be observed.


DB-A3 short Dimensions

Transport length

1225mm

ø Transport

344 mm



Position 1

Heigth min.

1210 mm

ø min



507 mm

Heigth max.

1909 mm

ø max

761 mm



Position 2

Heigth min.

1552 mm

ø min



958 mm

Heigth max.

1861 mm

ø max

1150 mm



Position 3

Heigth min.

1132 mm

ø min



992 mm

Heigth max.

1772 mm

ø max

1606 mm



Unit of measurement in drawings in mm
(Drawings not true to scale)