



Datasheet

Webbing Lanyard

according to EN 354:20010



IKV 11 (EN 362:2004)



IKV 06 (EN 362:2004)

Product information:

Order No.:	Length	Connection element	Opening gate (Carabiner)	Weight
45-IK 6 B 100 6	1,00 m	IKV 06	18 mm	0,54 kg
45-IK 6 B 150 6	1,50 m	IKV 06	18 mm	0,57 kg
45-IK 6 B 175 6	1,75 m	IKV 06	18 mm	0,58 kg
45-IK 6 B 200 6	2,00 m	IKV 06	18 mm	0,6 kg
45-IK 2 B 100 2	1,00 m	IKV 11	26 mm	0,32 kg
45-IK 2 B 150 2	1,50 m	IKV 11	26 mm	0,35 kg
45-IK 2 B 175 2	1,75 m	IKV 11	26 mm	0,36 kg
45-IK 2 B 200 2	2,00 m	IKV 11	26 mm	0,38 kg

Features:

Connecting component in a restraint system

- 25 mm wide webbing made of polyester (abrasion resistant, dimensionally stable, light and weather resistant)
- Fitted with a small aluminium double action hook IKV 11 with a 25 mm opening gate at each end *or*
- or:*
- Steel snap hook IKV 06 (EN 362: 2004) at both ends
- Connecting means and parts of a PSAgA collection system

Application:

Connect, Restraint

Areas of use:

Industry