

Adjustable Webbing Lanyard

according to EN 358:2000



IKV 11 (EN 362:2004)



IKV 06 (EN 362:2004)

Product information:

Order No:	Length	Connection element	Opening gate (Carabiner)	Weight
45-IK 6 B 100 A 6	1,00 m	IKV 06	18 mm	0,67 kg
45-IK 6 B 150 A 6	1,50 m	IKV 06	18 mm	0,59 kg
45-IK 6 B 175 A 6	1,75 m	IKV 06	18 mm	0,59 kg
45-IK 6 B 200 A 6	2,00 m	IKV 06	18 mm	0,60 kg
45-IK 2 B 100 A 2	1,00 m	IKV 11	26 mm	0,35 kg
45-IK 2 B 150 A 2	1,50 m	IKV 11	26 mm	0,67 kg
45-IK 2 B 175 A 2	1,75 m	IKV 11	26 mm	0,37 kg
45-IK 2 B 200 A 2	2,00 m	IKV 11	26 mm	0,38 kg

Features:

Length-adjustable component in a workplace positioning system

- 25 mm wide webbing made of polyester (abrasion resistant, dimensionally stable, light and weather resistant)
- Length-adjustable holding rope of the PSAgA
- Aluminum double action hook IKV 11 (EN 362: 2004) at both ends
- or:**
- Steel double action hook IKV 06 (EN 362: 2004) at both ends

Application:

Restraint of work positioning

Areas of use:

Industrial, construction, scaffolding and utility environments