

Adjustable Webbing Lanyard

according to EN 358:2000



IKV 03 (EN 362:2004)



IKV 06 (EN 362:2004)



IKV 11 (EN 362:2004)

Product information:

Order No.:	Length	Connection element	Opening gate (carabiner)	Weight
45-IK 6 B 100 A 3	1,00 m	IKV 06 / IKV 03	18 mm / 60 mm	0,78 kg
45-IK 6 B 150 A 3	1,50 m	IKV 06 / IKV 03	18 mm / 60 mm	0,82 kg
45-IK 6 B 175 A 3	1,75 m	IKV 06 / IKV 03	18 mm / 60 mm	0,84 kg
45-IK 6 B 200 A 3	2,00 m	IKV 06 / IKV 03	18 mm / 60 mm	0,85 kg
45-IK 2 B 100 A 3	1,00 m	IKV 11 / IKV 03	26 mm / 60 mm	0,67 kg
45-IK 2 B 150 A 3	1,50 m	IKV 11 / IKV 03	26 mm / 60 mm	0,71 kg
45-IK 2 B 175 A 3	1,75 m	IKV 11 / IKV 03	26 mm / 60 mm	0,73 kg
45-IK 2 B 200 A 3	2,00 m	IKV 11 / IKV 03	26 mm / 60 mm	0,74 kg

Features:

Length-adjustable component in a workplace positioning system

- 25 mm wide webbing made of polyester (abrasion resistant, dimensionally stable, light and weather resistant)
 - Length-adjustable holding rope of the PSAGa
 - Aluminum tube hook IKV 03 (EN 362: 2004) at the end
 - Aluminum snap hook IKV 11 (EN 362: 2004) at the end
- or:**
- Steel snap hook IKV 06 (EN 362: 2004) at the end

Application:

Restraint of work positioning

Areas of use:

Industrial, construction, scaffolding and utility environments