

Kernmantle Rope Energy Absorbing Lanyard

according to EN 354:2010; EN 355:2002



IKV 55 (EN 362:2004)



IKV 06 (EN 362:2004)



IKV 11 (EN 362:2004)

Product information:

Order No.:	Length	Connection element	Opening gate (Carabiner)	Weight
45-IK 6 FK 100 3	1,00 m	IKV 06 / IKV 55	18 mm / 61 mm	1,13 kg
45-IK 6 FK 150 3	1,50 m	IKV 06 / IKV 55	18 mm / 61 mm	1,15 kg
45-IK 6 FK 175 3	1,75 m	IKV 06 / IKV 55	18 mm / 61 mm	1,16 kg
45-IK 6 FK 200 3	2,00 m	IKV 06 / IKV 55	18 mm / 61 mm	1,17 kg
45-IK 2 FK 100 3	1,00 m	IKV 11 / IKV 55	26 mm / 61 mm	1,02 kg
45-IK 2 FK 150 3	1,50 m	IKV 11 / IKV 55	26 mm / 61 mm	1,04 kg
45-IK 2 FK 175 3	1,75 m	IKV 11 / IKV 55	26 mm / 61 mm	1,05 kg
45-IK 2 FK 200 3	2,00 m	IKV 11 / IKV 55	26 mm / 61 mm	1,06 kg

Features:

Webbing energy absorbing lanyard

- Kernmantle rope energy absorbing lanyard Ø 11 mm made of polyamid (abrasion resistant, dimensionally stable, light and weather resistant)
- Aluminum double action hook IKV 55 (EN 362:2004) at the end
- Aluminum double action hook IKV 11 (EN 362:2004) at the energy absorbing lanyard
- or:**
- steel double action hook IKV 06 (EN 362:2004) at the energy absorbing lanyard

Applikation:

For use in fall arrest systems

Areas of use:

Industrial, construction and utility environments