

Adjustable Work Positioning Lanyard IK SK 01

according to EN 358:2000



IKV 06 (EN 362:2004)



IKV 11 (EN 362:2004)



IKV 30 (EN 362:2004)

Product information:

Order No:	Lenght	Connection element	Opening gate (Carabiner)	Weight
45-IK 30 WLK 150 6	1,50 m	IKV30 / IKV 06	17mm / 18 mm	1,12 kg
45-IK 30 WLK 175 6	1,75 m	IKV30 / IKV 06	17mm / 18 mm	1,20 kg
45-IK 30 WLK 200 6	2,00 m	IKV30 / IKV 06	17mm / 18 mm	1,28 kg
45-IK 30 WLK 150 2	1,50 m	IKV 30 / IKV 11	17 mm / 26 mm	1,01 kg
45-IK 30 WLK 175 2	1,75 m	IKV 30 / IKV 11	17 mm / 26 mm	1,09 kg
45-IK 30 WLK 200 2	2,00 m	IKV 30 / IKV 11	17 mm / 26 mm	1,17 kg

Features:

Length-adjustable component in a workplace positioning system

- Kernmantle rope Ø 12 mm made of polyamid (Abrasion-proof, dimensionally stable, light- and weather-resistant)
- 0,50 m rope protection made of polyester
- Adjustable lanyard clamp IK SK 01 made of galvanized steel
- Steel carabiner hook IKV 30 (EN 362:2004) with Trilock-Protection at the adjustable lanyard clamp
- Steel carabiner hook IKV 06 (EN 362:2004) at the end of the rope
- or:**
- Double action hook IKV 11 (EN 362:2004) made of aluminum at the end

Application:

Connecting

Areas of use:

Work place positioning