


Flexible HWB 2,8 R DW 55

according to EN 360:2002



IKV 55 (EN 362:2004-T)



Explanations of the device names:

- H** = Retractable type fall arrester
- W** = Swivel attachment point
- S** = Steel lifeline
- B** = Webbing lifeline
- P** = Plastic housing
- Number** = Insert length of the device



IKAR retractable type fall arrester have been successfully tested in a simulated fall trial over and edge according to CNB/P/11.060 ($r \geq 0,5$ mm).

Product information:

| Order No: | Application length | Housing | Weight | Dimensions (LxBxT) | Connector (L _K) IKV 55 |
|--------------------|--------------------|-----------|---------|--------------------|---------------------------------------|
| 41-HWB 2,8 R DW 55 | 2 x 2,8 m | Aluminium | 3,90 kg | 603 x 190 x 70 mm | 248,0 mm |

Features

Twin retractable type fall arrester to protect 1 person.

- Sturdy and low-maintenance Retractable type fall arrester with dual swivel suspension.
- Enables reciprocal action for a secured change of work position within the guidelines of the EU regulation 2016/425.
- Robust aluminum housing with a rotational attachment eye.
- The rotatable Twinadapter TA 05 is designed for connection to a IKAR full body harness with an attachment tunnel.
- The rotatable Twinadapter prevents the twisting of the single strap and of the two webbings together.
- Lifeline made of Dyneema® webbing. The lifeline is tested over a double sharp edge.
- Standard connector IKV 55 .
- Nominal load: 136 kg
- Temperature range of application: -40°C bis +50°C
- Lifespan: approx 10 years