


Safety Harness IK G2 BR


according to EN 361:2002; EN 1497:2007



D-Ring (steel)



Quick release buckles (steel)



Quick-release fastener with climbing protection eyelet (chest), made of forged steel.

Product information:

Order No.:	Size	Fall arrest D-Ring chest	D-Ring at the back	D-Ring	Waistbelt	Weight
45-IK G 2 B R a	M - XL	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			1,60 kg

Features & fields of application:

Safety- and rescue harness with 2 D-Rings and quick-release buckles

- 45 mm wide webbing made of polyester (PES)
- 1 Rescue and fall arrest loop*
- 1 D-Ring in the back (shoulder area) made of forged steel
- 1 D-Ring in the chest area (climbing protection eyelet) made of forged steel
- Quick connect fastenings make the harness easy to fit and remove
- Individual size adjustment by leg and shoulder straps
- Nominal load: 136 kg
- Temperature range of application: -40°C bis +50°C
- Life service: approx. 10 years

* A fall arrest device with recovery mechanism (HRA) may be attached to this point when used in the vertical application providing the lifeline is attached from directly above i.e. confined space entry applications.

Application:

Fall arrest, restraint

Areas of use:

Industrial use, entry into confined spaces, sewage engineering